

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Starbond EM-150 Medium

**1.2. Intended Use of the Product Use of the Substance/Mixture:** Bonding, finishing, stabilizing, gap-filling.

### 1.3. Name, Address, and Telephone of the Responsible Party:

**Company**

CPH International 1450 W.

228th St. Suite 11

Torrance, CA 90005

T: 213-382-7788

T: 1-800-900-4583 (GLUE)

[www.starbond.com](http://www.starbond.com)

**Manufacturer**

Starbond 1450 W. 228th St.

Suite 11

Torrance, CA 90005

T: 213-382-7788

T: 1-800-900-4583 (GLUE)

[www.starbond.com](http://www.starbond.com)

### 1.4. Emergency Telephone Number

**Emergency Number:** 1-800-900-4583 (GLUE)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture GHS-US Classification

Acute Tox. 4	H332
(Inhalation: dust mist)	H315
Skin Irrit. 2	H319
Eye Irrit. 2	H317
Skin Sens. 1	H351
Carc. 2	H335
STOT SE 3	

Full text of hazard classes and H-statements: see Section 16.

### 2.2. Label Elements

#### GHS-US Labeling

**Hazard Pictograms (GHS-US) :**



**Signal Word (GHS-US)**

Warning

**Hazard Statements (GHS-US)**

- H315 - Causes skin irritation.
- H317 - May cause an allergic skin reaction.
- H319 - Causes serious eye irritation.
- H332 - Harmful if inhaled.
- H335 - May cause respiratory irritation.
- H351 - Suspected of causing cancer.

**Precautionary Statements (GHS-US)**

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P261 - Avoid breathing vapors, mist, or spray.
- P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves, protective clothing, and eye protection.

# Starbond EM-150 Medium

## Safety Data Sheet

Date Prepared: April 24, 2023

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see Section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixture

Name	Product Identifier	%
Ethyl 2 cyanoacrylate	(CAS-No.) 7085-85-0	> 86
Poly Methyl Methacrylate	(CAS-No.) 9011-14-7	10~13
Hydroquinone	(CAS-No.) 123-31-9	< 0.2

Full text of H-phrases: see Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes.

Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Harmful if inhaled. Skin sensitization. Suspected of causing cancer.

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. **Chronic Symptoms:** Suspected of causing cancer.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

# Starbond EM-150 Medium

Safety Data Sheet

Date Prepared: April 24, 2023

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Carbon dioxide, dry chemical.

**Unsuitable Extinguishing Media:** Application of water to product may generate heat and increase fire intensity.

### 5.2. Special Hazards Arising from the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Oxides of carbon, oxides of nitrogen, irritating organic vapors.

**Other Information:** Do not allow run-off from firefighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE). **Emergency**

**Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

**Methods for Cleaning Up:** Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Rapid exothermic polymerization occurs in the presence of water, amines, alkalis and alcohols.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. **Incompatible Materials:** Water, alcohol, amines, and alkalis.

### 7.3. Specific End Use(s)

# Starbond EM-150 Medium

Safety Data Sheet

Date Prepared: April 24, 2023

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in Section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Ethyl cyanoacrylate (7085-85-0)		
USA ACGIH	ACGIH TWA (ppm)	0.2 ppm
Hydroquinone (123-31-9)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	dermal sensitizer, Confirmed Animal Carcinogen with Unknown relevance to humans
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

### 8.2. Exposure Controls

**Appropriate Engineering Controls** : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released.

**Personal Protective Equipment** : Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing** : Chemically resistant materials and fabrics.

**Hand Protection** : Wear protective gloves.

**Eye and Face Protection** : Chemical safety goggles.

**Skin and Body Protection** : Wear suitable protective clothing.

**Respiratory Protection** : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information** : When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	Liquid
Appearance	Weak Yellow Transparent
Odor	Pungent Odor
Odor Threshold	1-2 ppm
pH	Not applicable
Evaporation Rate	No data available
Melting Point	No data available
Freezing Point	< -30 °C (< -22 °F)
Boiling Point	54 - 56 °C (129.2 - 132.8 °F)
Flash Point	> 84 °C (> 183.2 °F) [Test Method: Closed Cup]
Auto-ignition Temperature	485 °C (905 °F)
Decomposition Temperature	No data available
Flammability (solid, gas)	No data available
Vapor Pressure	< 0.27 kPa @ 25 °C (77 °F)
Relative Vapor Density at 20°C	4.3
Relative Density	No data available
Density	1 - 1.1 g/ml
Solubility	Insoluble in Water; Soluble in Acetone
Partition Coefficient N-Octanol/Water	No data available
Viscosity	100-200 mPa.s(20°C)

### 9.2. Other Information

# Starbond EM-150 Medium

Safety Data Sheet

Date Prepared: April 24, 2023

No additional information available

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** Stable usually

**10.2. Chemical Stability:** Material polymerizes rapidly by contact with water, alcohol, amines, and alkalis.

**10.3. Possibility of Hazardous Reactions:** The hazardous reaction is not caused under normal condition.

**10.4. Conditions to Avoid:** High temperature, Heating, Hot sources, Open flames.

**10.5. Incompatible Materials:** Oxidizing agents. Water, Alcohol, Amines, Alkalis.

**10.6. Hazardous Decomposition Products:** None expected under normal conditions of use.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Inhalation, dust, mist: Harmful if inhaled.

Starbond EM-150 Medium	
ATE (Dust/Mist)	1.52 mg/l/4h
Ethyl cyanoacrylate (7085-85-0)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	< 5.275 mg/l/4h U.S. Environmental Protection Agency December, 2014-converted to 4-hour exposure from 1 hour exposure.
ATE (Dust/Mist)	1.50 mg/l/4h
Hydroquinone (123-31-9)	
LD50 Oral Rat	298 mg/kg
LD50 Dermal Rabbit	74800 mg/kg
IARC group	3
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer.

**Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Symptoms/Injuries After Skin Contact:** Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. **Chronic Symptoms:** Suspected of causing cancer.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Hydroquinone (123-31-9)	
LC50 Fish 1	0.044 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 1	0.29 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.044 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
NOEC Chronic Crustacea	0.003 mg/l
NOEC Chronic Algae	0.0015 mg/l

# Starbond EM-150 Medium

Safety Data Sheet

Date Prepared: April 24, 2023

## 12.2. Persistence and Degradability

Starbond EM-150 Medium	
Persistence and Degradability	Not established.

## 12.3. Bioaccumulative Potential

Starbond EM-150 Medium	
Bioaccumulative Potential	Not established.
Hydroquinone (123-31-9)	
BCF Fish 1	40
Log Pow	0.5

## 12.4. Mobility in Soil

No additional information available

## 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name:** COMBUSTIBLE LIQUID, N.O.S., (Ethyl cyanoacrylate)

**Identification Number:** NA1993

**Packing Group:** III

**ERG Number:** 128

### 14.2. In Accordance with IMDG

Not regulated for transport

### 14.3. In Accordance with IATA

**Proper Shipping Name:** AVIATION REGULATED LIQUID, N.O.S., (Ethyl cyanoacrylate)

**Packing Group:** III

**Identification Number:** UN3334 **Hazard Class:** 9

**Label Codes:** 9

**ERG Code (IATA):** 9A



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

Starbond EM-150 Medium	
Ethyl 2 cyanoacrylate (7085-85-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Hydroquinone (123-31-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 - 10000 lb
SARA Section 313 - Emission Reporting	1 %

# Starbond EM-150 Medium

Safety Data Sheet

Date Prepared: April 24, 2023

## 15.2. US State Regulations

<b>Ethyl 2 cyanoacrylate (7085-85-0)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Hydroquinone (123-31-9)</b>
U.S. - Massachusetts - Right to Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Other Information:** This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

### GHS Full Text Phrases:

Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)



# Starbond Instant Set Accelerator (Activator) for CA Super Glue, 6 oz. Aerosol

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 06/17/2022 Date of Issue: 06/29/2022

### Section 1: Identification

#### Product Identifier

**Product Form:** Mixture **Product Name:** Starbond Instant Set Accelerator (Activator) for CA Super Glue, 6 oz. Aerosol

#### Intended Use of the Product

**Use of the Substance/Mixture:** To speed up the drying time of super glues

#### Name, Address, and Telephone of the Responsible Party

**Company**  
CPH International  
1450 W. 228th St. Suite #11,  
Torrance, CA 90501  
T: 213-382-7788  
www.starbond.com

**Manufacturer**  
Starbond  
1450 W. 228th St. Suite #11,  
Torrance, CA 90501  
T: 213-382-7788

#### Emergency Telephone Number : :

(800) 424-9300 (Chemtrec- US)  
(703) 527-3887 (International - Call Collect)

### Section 2: Hazard(s) Identification

#### Classification of the Substance or Mixture

##### GHS Hazards Category

Flammable liquid	- Category 2
Eye Irritation	- Category 2A
Skin Irritation	- Category 2
Respiratory Irritation	- Category 3
Specific Target Organ Toxicity	- Category 2

##### Label Elements

GHS-US Labeling Hazard Pictograms (GHS-US) :





## Section 2: Hazard(s) Identification

**Signal Word Hazard Statements** **⚠ DANGER**: Highly Flammable, Irritating to eye and skin

Harmful, Danger of serious damage to health by prolonged exposure through inhalation  
Possible risk of harm to unborn child

Harmful: may cause lung damage if swallowed

**Precautionary Statements :**

### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Store in a well-ventilated place. Keep container tightly closed.

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist/vapors/spray. Use only outdoors or in a well-ventilated area. Vapor may cause drowsiness and dizziness.

### Response

#### Inhalation

Move the victim to a fresh air place immediately. Get medical attention if discomforts persist.

#### Ingestion

Rinse mouth with clean water immediately.

DO NOT induce vomiting.

Get medical attention immediately.

If vomiting occurs, keep the victim's head low so that vomits from the stomach will not enter the lungs.

#### Skin Contact

Remove contaminated clothing and flush the affected skin areas with clean water for at least 15 minutes. Get medical attention if discomforts persist.

#### Eye Contact

Make sure all contact lenses are removed before flushing the eyes with eye lids open with clean water for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

**Section 2: Hazard(s) Identification**

**Storage**

Store in a well-ventilated Place. Keep container tightly closed. Keep cool. Store in a locked cabinet, cage or room.

**Disposal**

Dispose of contents and container in accordance with all local, regional, national and international regulations.

CLASSIFICATION (1999/45) XI, F, R11, R36, R66, R67

This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.  
Highly flammable. Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed. Vapors may cause drowsiness and dizziness.

**Section 3: Composition / Information on Ingredients**

Name	EC No.	Cas No.	Content %	GHS Classification
Organic Activator	Trade Secret (*)	Trade Secret (*)	0-5%	T, R23/24/25, R33, R52/53, S28A, S36/37, S45, S61
Petroleum Gas, Liquefied, Sweetened	270-705-8	Trade Secret (*)	0-50%	F+, T, R12, R45, S45, S53
Organic Solvent	Trade Secret (*)	Trade Secret (*)	50-100%	XI, F, R11, R36, R66, R67, S16, S26, S9

The Full Text for all R-Phrases and S-Phrases is displayed in Section 15

**COMPOSITION COMMENTS**

The data shown are in accordance with the latest EC Directives

## Section 4: First-Aid Measures

### Emergency and First Aid Procedures

**Eyes:** If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Swallowing:** Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation:** If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention

**Note to Physicians:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (i.e., asthma-like conditions), bloodforming system.

## Section 5: Fire-Fighting Measures

### Extinguishing Media

Alcohol foam, carbon dioxide, dry chemical.

### Special Firefighting procedures

Water may be ineffective. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full coverage face piece operated in the positive-pressure demand mode with appropriate turnout gear and chemical resistant personal protective equipment.

### Unusual fire and explosion hazards

Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Flammable material



## Section 6: Accidental Release Measures

### Personal Precautions

Wear protective clothing as described in Section 8.

### Environmental Precautions

Spillages or uncontrolled discharges into watercourses must immediately be alerted to Environmental Agency or other appropriate regulatory authority

### Spill clean up methods

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, open flames, and smoking. Ventilate. Absorb in vermiculite, dry sand, or earth and place into containers for disposal.

## Section 7: Handling and Storage

### Usage Precautions:

Keep away from heat, sparks and open flames. Avoid spilling, skin and eyes contact. Use with adequate ventilation and avoid excessive exposure to solvent vapors. Use approved respirator if air contamination exceeds the accepted level

### Storage Precautions:

FLAMMABLE/Combustible. Keep away from oxidizers, open flames and other ignition sources. Keep unused contents in original container and tightly closed lids. Store in a cool, dry and well-ventilated place and at an ambient Temperature not to exceeding above 120o F

### Storage Class:

FLAMMABLE liquid storage

## Section 8 : Exposure controls / Personal Protection

### Notice :

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

### Inhalation health risk and symptoms of exposure:

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: mouth and throat irritation (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, high blood sugar, coma.

### Section 8 : Exposure controls / Personal Protection

#### **Skin and eye contact health risks and symptoms of exposure:**

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

#### **Ingestion health risks and symptoms of exposure:**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

#### **Health hazards (acute and chronic):**

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects, mild, reversible kidney effects, blood abnormalities. This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

**Carcinogenicity:** NTP Carcinogen: N/A IARCH monographs: N/A

OSHA regulated: N/A

#### **Medical conditions generally aggravated by exposure to this product:**

Preexisting eye, skin, heart, central nervous system and respiratory disorders may be aggravated by exposure to this product.

#### **Emergency and First Aid Procedures**

**Eyes:** If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin:** Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Section 8 : Exposure controls / Personal Protection**

**Swallowing:** Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation:** If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention

**Note to Physicians:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (i.e., asthma-like conditions), bloodforming system.

Name	Work Exposure Limits	Remarks
Organic activator	Not Listed	Consult local authorities for occupational exposure
Organic solvent	NIOSH: 250 ppm TWA; 590 mg/m3 TWA 2500 ppm IDLH (10% LEL) ACGIH: 500 ppm TWA; 750 ppm STEL OSHA-Final PELs: 1000 ppm TWA; 2400 mg/m3 TWA	Same as above
Petroleum Gas, Liquefied, Sweetened	ACGIH: Not Listed NIOSH: Not Listed OSHA-Final PELs: Not Listed	Same as above



**Section 8 : Exposure controls / Personal Protection**

**Protective Equipment:**

**Process conditions:** Provide eyewash station.

**Engineering Measures:** Provide adequate ventilation. Fully equipped spray booth is recommended to ensure the workers legal exposure limits are not exceeded.

**Respiratory equipment:** Wear respirator with appropriate cartridge for organic solvents and chemicals.

**Hand protection:** Wear approved gloves such as Neoprene, Nitrile or Rubber types

**Eye protection:** Wear splash-proof goggles

**Other protection:** Wear appropriate clothing to prevent any possible skin contact

**Hygiene measures:** DO NOT SMOKE IN THE WORK AREA. Wash at the end of each work shift and before eating, drinking or smoking. Promptly remove contaminated clothing.

**Section 9 : Physical and Chemical Properties**

<b>Appearance</b>	: Liquid
<b>Color</b>	: Colorless
<b>Odor</b>	: Mild/Sweet Characteristics
<b>Boiling Point</b>	: 208 °F
<b>Relative Density</b>	: 0.735 g/mL
<b>Vapor Density</b>	: 3.1 (Air = 1)
<b>Flash Point</b>	: 25 °F [Test Method: Closed Cup]
<b>Flammable Limit</b>	: NA (Lower %) NA (Upper %)
<b>Solubility Value</b>	: (g/100g H2O @ 20oC)
<b>Volatile Organic Compound</b>	: 20% from Aerosol Propellant

**Section 10 : Stability and Reactivity**

<b>Stability</b>	: Stable
<b>Conditions to avoid</b>	: Heat, fires, and ignition sources
<b>Incompatibility (Materials to avoid)</b>	: Avoid contact with acids, strong oxidizing agents
<b>Hazardous composition or byproducts</b>	: May form carbon dioxide and carbon monoxide
<b>Hazardous polymerization</b>	: Will not undergo hazardous polymerization



### Section 11 : Toxicological Information

#### Organic activator:

Carcinogenicity: Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.

Routes of Entry: Absorbed through skin. Dermal contact. Eye contact.

Toxicity to Animals: WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute toxicity of the vapor (LC50): 1400 mg/m<sup>3</sup> 4 hours [Rat]. 3

Chronic Effects on Humans: Not available.

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation.

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans: May affect genetic material (mutagenic)

Special Remarks on other Toxic Effects on Humans:

Acute Potential Health Effects: Skin: May cause skin irritation. May be harmful if absorbed through skin. Eyes: May cause eye irritation. Inhalation: May cause respiratory tract irritation. May affect respiration (dyspnea, respiratory stimulation). Harmful if inhaled.

Ingestion: May cause gastrointestinal tract irritation with nausea, vomiting, and diarrhea.

Harmful if swallowed. The toxicological properties of this substance have not been fully investigated. Chronic Potential Health Effects: There is a danger of cumulative effects

#### Organic solvent :

LD50/LC50: Dermal, guinea pig: LD50 = >9402 uL/kg; Draize test, rabbit, eye: 20 mg Severe; Draize test, rabbit, eye: 20 mg/24H Moderate; Draize test, rabbit, eye: 10 uL Mild; Draize test, rabbit, skin: 503 mg/24H Mild; inhalation, mouse: LC50 = 44 gm/m<sup>3</sup>/4H; Inhalation, rat: LC50 = 50120 mg/m<sup>3</sup>/8H; Oral, mouse: LD50 = 3 gm/kg; Oral, rabbit: LD50 = 5330 mg/kg; Oral, rat: LD50 = 5800 mg/kg; Carcinogenicity: Not listed by ACGIH, IARC, NTP, or CA Prop 65. Epidemiology: In a series of studies, no statistically significant differences in causes of

athinical laboratory results were observed in 948 employees exposed to up to 1070 ppm organic solvent

effects in the offspring of animals exposed to doses which also produced significant maternal toxicity. Reproductive Effects: During the Stewart et al. study, four adult female volunteers were exposed 7.5 hours to vapor at a nominal concentration of 1000 ppm. Three of the four women experienced premature menstrual periods which were attributed to the exposure.

Mutagenicity: Sex chromosome loss and nondisjunction(Yeast - Saccharomyces cerevisiae) = 47600 ppm; Cytogenetic analysis(Rodent - hamster Fibroblast)= 40 gm/L. Neurotoxicity: No information found

#### Petroleum gases, liquefied, sweetened (CAS#68476-86-8):

acute toxicity of the vapor (LC50): 1400 mg/m<sup>3</sup> 4 hours [Rat]. 3

P  
C



## Section 12 : Ecological Information

### **Organic activator:**

Ecotoxicity: Not available. BOD5 and COD: Not available. Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. Toxicity of the Products of Biodegradation: The products of degradation are less toxic than the product itself. Special Remarks on the Products of Biodegradation: Not available

### **Organic solvent :**

Ecotoxicity: Fish: Rainbow trout: 5540 mg/l; 96-hr; LC50Fish: Bluegill/Sunfish: 8300 mg/l; 96-hr; LC50 No data available. Environmental: Volatilizes, leeches, and biodegrades when released to soil. TERRESTRIAL FATE: If released on soil, will both volatilize and leach into the ground. Readily biodegrades and there is evidence suggesting that it biodegrades fairly rapidly in soils. AQUATIC FATE: If released into water, will probably biodegrade. It is readily biodegradable in screening tests, although data from natural water are lacking. It will also be lost due to volatilization (estimated half-life 20 hr from a model river). Adsorption to sediment should not be significant. Physical: ATMOSPHERIC FATE: In the atmosphere, will be lost by photolysis and reaction with photochemically produced hydroxyl radicals. Half-life estimates from these combined processes are 79 and 13 days in January and June, respectively, for an overall annual average of 22 days. Therefore considerable dispersion should occur. Being miscible in water, wash out by rain should be an important removal process. This process has been confirmed around Lake Shinsei-ko in Japan. There was found in the air and rain as well as the lake

### **Petroleum gases, liquefied, sweetened (CAS#68476-86-8):**

Ecotoxicity - Component Analysis - Ecotoxicity - Aquatic Toxicity No ecotoxicity data are available for this product's components

## Section 13 : Disposal Considerations

### **Waste Treatment Methods**

Hazardous wastes should be sent to a RCRA approved incinerator or disposed of in a RCRA approved waste facility. Dispose of container and unused contents in accordance with federal, state and local requirements. CAS# 99-97-8 DMPT is listed on the TSCA inventory.

I certify that all chemicals in this shipment comply with all applicable rules or orders under TSCA and that I am not offering a chemical substance for entry in violation of TSCA or any applicable rule or order under TSCA.

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Revision Date: 04 /07/2022 Date of Issue: 04/14/2022

### Section 14 : Transport Information

AD R/RID PROPER SHIPPING NAME : UN1950 Aerosol  
PRIMARY HAZARD CLASS/DIVISION : 2.1  
UN /UA Number : UN1950  
Packing Group  
Note: Small Containers LIMITED QUANTITY except: tition.

IMO Proper Shipping Name : UN 1950 AEROSOL  
IMO UN class : 2.1  
IMO UN class : 1950  
IMO Packing Group : II  
IMO Label : Flammable Gas  
IMO Vessel Stowage : E  
IATA PROPER SHIPPING NAME : UN 1950  
UN HAZARD CLASS/DIVISION : 2.1  
UN /NA NUMBER : 1950  
IATA PACKING GROUP : II  
IATA LABEL : FLAMMABLE GAS  
IATA STOWAGE : ACCESSIBLE

Special Precautions for User: AVOID HIGH TEMPERATURES.

GHS Label:



DANGER CONTENTS UNDER PRESSURE. HIGHLY FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL. CAUSES SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL OR FATAL IF SWALLOWED AND ENTERS AIRWAYS. HARMFUL TO AQUATIC LIFE. Refer to SDS for additional information on safe handling / use. - Keep out of reach of children. For Industrial Use Only.

Contents: Organic activator, organic solvent, and Sweetened Liquefied Petroleum Gas. This product contains one or more chemicals known to the State of California to cause cancer, birth defects, and/or other reproductive harm.

Hazards : H220: Extremely Flammable Gas. H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation. H280: Contains gas under pressure, may explode if heated. H340: May cause genetic defects. H301: Toxic if swallowed. H331: Toxic if inhaled. H311: Toxic in contact with skin. H336: May cause drowsiness or dizziness. H373: May cause damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects.

### Section 14 : Transport Information

**Precautionary Statement(s):** P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P280: Wear protective gloves/protective clothing/eye protection/face protection. P240: Ground/bond container and receiving equipment. P271: Use only outdoors or in a well-ventilated area. P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+340+312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**First Aid: Inhalation** - Move person to fresh air. If symptoms occur obtain medical attention. **Skin Contact** - Wash affected skin with soap and water. If symptoms occur obtain medical attention.

**Eye Contact** - If substance has got into the eyes, immediately wash out with plenty of water for at least 15 minutes. If symptoms occur obtain medical attention.

**Ingestion** - Do not induce vomiting. Drink one glass of water. If symptoms occur obtain medical attention

### Section 15 : Regulatory Information

#### **Hazard**

H220: Extremely Flammable Gas.  
H225: Highly flammable liquid and vapour.  
H280: Contains gas under pressure, may explode if heated.  
H301: Toxic if swallowed.  
H311: Toxic in contact with skin.  
H319: Causes serious eye irritation.  
H331: Toxic if inhaled.  
H336: May cause drowsiness or dizziness.  
H340: May cause genetic defects.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H412: Harmful to aquatic life with long lasting effects.

#### **Precautionary Statement(s):**

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P240: Ground/bond container and receiving equipment.  
P271: Use only outdoors or in a well-ventilated area.

### Section 15 : Regulatory Information

#### P recautionary Statement(s):

P 303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

R inse skin with water/shower.

P 304+340+312: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P 305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

#### R -Phrases:

R 11: Highly Flammable

R 12: Extremely flammable

R 23/24/25: Toxic by inhalation, in contact with skin and if swallowed

R 33: Danger of cumulative effects

R 36: Irritating to eyes

R 45: May cause cancer

R 52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R 66: Repeated exposure may cause skin dryness or cracking

R 67: Vapors may cause drowsiness and dizziness

#### S -Phrases:

S 9: Keep container in a well-ventilated place

S 16: Keep away from sources of ignition - No smoking

S 26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S 28A:

After contact with skin, wash immediately with plenty of water

S 36/37: Wear suitable protective clothing and gloves

S 45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)

S 53: Avoid exposure - obtain special instructions before use

S 61: Avoid release to the environment. Refer to special instructions/safety data sheets

### Section 16 : Other Information

#### Disclaimer

Above information is based on data supplied to us and is believed to be correct. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose. It is the user's obligation to determine the safe use of it.